

Obv!os[®] Glaive

POS Terminal

Obv!os[®] presents the Glaive series, a range of POS terminals that set a new benchmark in the world of purpose built retail hardware.

The Glaive is the first terminal of its type to successfully offer a stand-alone or client server configuration, at a price point that will convert many to its sleek and practical design.

Visit our website for more information
www.obvios.com



Obvios® Glaive



PRODUCT DESCRIPTION

Continuing in the tradition of the Obvios range, the Glaive is encased in die-cast aluminium and offers the robust and durable quality you have come to expect from this market leading brand.

The Glaive is a fanless terminal capable of running the latest embedded operating systems and is built to comply with the rigorous IP65 environmental rating.

Available with a Celeron processor, the Glaive performs equally well with disk-based OS applications, or the embedded environment of WinCE, XP and Linux. With native wireless support and a range of screen configurations, Glaive is your first choice for state-of-the-art terminal performance.

APPLICATIONS

POINT OF SALE

EFTPOS

RETAIL

HOSPITALITY

MANUFACTURING

HOME AUTOMATION

ACCESS CONTROL

RT560 SERIES SPECIFICATIONS

Construction	Die-cast Aluminium Casing
Display	12.1" 800x600 TFT colour display 15.1" 1024x768 TFT colour display
Touch Panel	ELO 5-wire resistive touch screen
CPU	Celeron (400/650 MHz)*
RAM	256MB SD RAM
Solid State Disk	Compact Flash (Optional)
LAN	10/100 BaseT Ethernet
Serial Ports	Three RS-232C serial ports COM1/2 RS-232C in 9-pin D-sub male (Pin 9 may set to supply +5V or +12V) COM2 may be set as RS-422/RS-485 COM4 (RJ-45)
VGA Port	One connector for external VGA monitor
Sound Port	Line out for powered speakers
USB Port	Three USB ports
Keyboard Port	PS/2 style keyboard port
Cash Drawer Port	One RJ-11 cash drawer port capable of driving two +12V drawers
Power Supply	External 60W power adapter with +24V DC output
Power Consumption	~40 to 50W
Dimensions	320 (W) x 235 (L) x 320(H) mm (12.1") 365 (W) x 235 (L) x 360 (H) mm (15")
Display Tilt	90° (upright) to 180° (flat)
Operating Temp.	5°C to 40°C
Compliance	CE, Class-B, TUV, FCC, UL, CSA, CTick
Operating Systems	DOS, Windows 98, NT, 2000, XP, WinCE, Linux (RedHat 7.3), XP Embedded

OPTIONS

Magnetic Card Reader (MCR)
Customer Vacuum Fluorescent Display (VFD)
32-key Keypad with I-button and MCR
Wireless 802.11b

* Specifications subject to change without notice.

Distributed by Obvios Ltd

USA

Suite 110, 2120 North Central
Phoenix, AZ 85004, USA
Tel: +1 888 706 9989 (TOLL FREE)
Tel: +1 301 519 1088
Email: sales@obvios.com

EUROPE

2 Station Approach
Bicester, Oxfordshire OX26 6BZ
UNITED KINGDOM
Tel: +44 1869 365 400
Email: sales@obvios.com

ASIA PACIFIC

Level 3, 39 Leighton Place
Hornsby, NSW 2077
AUSTRALIA
Tel: +61 2 9477 1999
Email: sales@obvios.com

Obvios® is a registered trademark

Internet: www.obvios.com

© Copyright 2005 Obvios Ltd

